

Application No. 10/023,652

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously Amended) A pixel driver circuit for a device like a diode, comprising:
- a first storage capacitor;
 - a first transistor of which a gate is connected to the storage capacitor; and
 - a unity gain buffer; and
- an input of the unity gain buffer being a voltage at one of a source and a drain of the transistor during a programming stage,
- wherein the unity gain buffer reproduces the voltage during a reproduction stage.
2. (Previously Amended) A pixel driver circuit as claimed in claim 1, wherein the unity gain buffer is implemented as an operational amplifier.
3. (Previously Amended) A pixel driver circuit as claimed in claim 1, wherein the buffer is connected to have unity gain.
4. (Previously Amended) A pixel driver circuit as claimed in claim 2, further comprising a second transistor so as to act as a current switch for storing voltage on a second capacitor.
5. (Previously Amended) A pixel driver circuit as claimed in claim 1, wherein the buffer comprises a differential pair circuit and a driver circuit.
6. (Previously Amended) A pixel driver circuit as claimed in claim 5, wherein the differential pair circuit comprises two transistors whose gates respectively provide an inverting input and a non-inverting input of the buffer and a further transistor whose gate provides a bias voltage input of the buffer.

Application No. 10/023,652

a storage capacitor;
a pixel element;
a transistor having a gate connected to the storage capacitor, the transistor operating as a current control; and
a unity gain buffer,
an input of the unity gain buffer being a voltage at one of a source and a drain of the transistor during a programming stage during which a data current for programming is supplied to the pixel driver circuit, and
the unity gain buffer reproducing the voltage during a reproduction stage during which a current corresponding to the data current is supplied through the transistor to the pixel element.

13. (Previously Presented) A pixel driver circuit, comprising:

a storage capacitor;
an organic electroluminescent element;
a transistor having a gate connected to the storage capacitor, the transistor operating as a current control; and
a unity gain buffer,
an input of the unity gain buffer being a voltage at one of a source and a drain of the transistor during a programming stage during which a data current for programming is supplied to the pixel driver circuit, and
the unity gain buffer reproducing the voltage during a reproduction stage during which a current corresponding to the data current is supplied through the transistor to the organic electroluminescent element.

14. (Currently Amended) A driving method for a display device that includes a pixel driving circuit having a pixel element, the method comprising:

Application No. 10/023,652

a programming stage during which a data current for programming is supplied to the pixel driver circuit; and

a reproduction stage during which a current corresponding to the data current is supplied to the pixel element;

wherein the method further comprises providing a unity gain buffer having an input and an output, and

during the programming stage, supplying to the input of the unity gain buffer a voltage at one of a source and drain of a transistor that controls a current supplied to the pixel element, and

during the reproduction stage, reproducing at the output of the unity gain buffer the voltage of one of the source and drain of the transistor.

15. (Currently Amended) The driving method according to claim 14, comprising the step of selecting the pixel element being an organic electroluminescent element.